



| Type | dw* mm | Mt kNm | D | I | L | a | b | c | t | Flange- bolts** Grade 12.9 | Ma Nm | Number of blots** |
|----------|----------------|----------------------|-----|----|----|-----|-------|----|-----|----------------------------------|----------|----------------------|
| 58 - 21 | 20 24 28 | 0,12 0,17 0,24 | 60 | 18 | 22 | 58 | 47 | 30 | 1,3 | M 5 X 16 | 9 | 4 |
| 65 - 21 | 20 24 30 | 0,16 0,22 0,33 | 72 | 20 | 24 | 65 | 52 | 35 | 1,5 | M 6 X 20 | 15 | 4 |
| 75 - 21 | 25 30 40 | 0,29 0,41 0,66 | 80 | 22 | 27 | 75 | 62 | 42 | 1,8 | M 6 X 20 | 15 | 6 |
| 90 - 21 | 30 40 45 | 0,38 0,59 0,8 | 100 | 26 | 31 | 90 | 74,5 | 47 | 2 | M 8 X 25 | 35 | 4 |
| 100 - 21 | 40 50 55 | 0,8 1,17 1,54 | 115 | 26 | 21 | 100 | 84 | 57 | 2 | M 8 X 25 | 35 | 6 |
| 120 - 21 | 40 60 70 | 1,73 3,03 4,24 | 138 | 28 | 34 | 120 | 101,5 | 75 | 2 | M 10 X 30 | 70 | 8 |
| 150 - 21 | 50 70 85 | 4 6,53 9,52 | 170 | 39 | 46 | 150 | 130 | 90 | 2 | M 10 X 30 | 120 | 8 |

Further size on request

Technical changes to be reserved without notice.

* dia dw can be chosen within the given limitations

** flange holes, bolts size and bolt quantity may be variant (dependent on the seller of carden shaft)

when ordering please state: SFN-8020, 120 – 21 X 65 X A
(Type X dw X MODEL)

additional: flange holes, bolt size and bolt quantity
if variant from catalogue